



Image for marketing purposes only.

POWERED BY EXCELLENCE

DIESEL GENERATOR 20 kVA

GENERATOR

MINING | INDUSTRIAL | UTILITIES | ELECTRICAL CONTRACTORS | MANUFACTURING | QUARRIES | CONSTRUCTION | EXPLORATION | MILITARY | SHIPPING | EVENTS

Generator Designation	CG-0020
Fleet Range	619-572; 570; 565-533

Dimensions

Length	1684 mm
Width	860 mm
Height	1460 mm
Weight Wet	923 kg
Weight Dry	880 kg
CSC Plated	No
Configuration	Canopy

Power Ratings

Engine	404D-22G
Prime 50Hz	20 kVA
Prime 50Hz @ 0.8 pf	16 kW
Prime 60 Hz	N/A
Prime 60Hz @ 0.8 pf	N/A
Max Load @ 0.8 pf/415 V	27.8 A

Fuel Consumption 50 Hz**

100% Load	5.3 kVA
75% Load	N/A
50% Load	N/A

Fuel Reserve 50 Hz**

Tank Size	44 L
100% Load	8.3 hr
75% Load	N/A
50% Load	N/A

Other

Sound Level	62.6 dB(A) @ 7 m
Temp Before Derate	30°C
Maximum Operating Temperature	50°C
Cooling Chamber Fan Type	Direct Drive
Parallel Controller	Inteli-Lite
Utility Configured	No
Telemetry	Yes

Notes

** Fuel data provided as per:
 - includes 1 hr in 12 @ 110% Load)
 - at prime rating
 - ASC- Cat Application Support Centre
 - dB(A) Ratings @ 100 % Load @ 50 Hz (± 2 dB(A) expected)

**ONE NETWORK.
ONE CALL 1800 800 441**
energypower.com.au

The information in this document may change without notice.
 CG-0020-V1-0616

**Energy Power
Systems**

