

Image for marketing purposes only.

### **POWERED BY EXCELLENCE**



# **GENERATOR**

MINING | INDUSTRIAL | UTILITIES | ELECTRICAL CONTRACTORS | MANUFACTURING | QUARRIES | CONSTRUCTION | EXPLORATION | MILITARY | SHIPPING | EVENTS

Generator Designation Fleet Range	CG-0080 791; 688-650
Dimensions	
Length	3280 mm
Width	1130 mm
Height	2100 mm
Weight Wet	3226 kg
Weight Dry	2660 kg
CSC Plated	No
Configuration	Canopy
Power Ratings	
Engine	1104C-44TAG2
Prime 50Hz	80 kVA
Prime 50Hz @ 0.8 pf	64 kW
Prime 60 Hz	N/A
Prime 60Hz @ 0.8 pf	N/A
Max Load @ 0.8 pf/415 V	111.2 A

#### Fuel Consumption 50 Hz\*\*

100% Load	20.3 L/hr
75% Load	N/A
50% Load	N/A

#### Fuel Reserve 50 Hz\*\* Tank Size 631 L 100% Load 31.0 hr 75% Load N/A 50% Load N/A Other Sound Level 65.9 dB(A) @ 7 m Temp Before Derate 40°C 41°C Maximum Operating Temperature Cooling Chamber Fan Type Direct Drive Parallel Controller Inteli-Lite Utility Configured No Telemetry Yes

Notes

\*\* Fuel data provided as per: - includes 1 hr in 12 @ 110% Load)

- at prime rating

- ASC- Cat Application Support Centre

- dB(A) Ratings @ 100 % Load @ 50 Hz ( $\pm$  2 dB(A) expected)

## ONE NETWORK. ONE CALL 1800 800 441

energypower.com.au

The information in this document may change without notice. CG-0080-V1-0616

