

Image for marketing purposes only.

POWERED BY EXCELLENCE



GENERATOR

MINING | INDUSTRIAL | UTILITIES | ELECTRICAL CONTRACTORS | MANUFACTURING | QUARRIES | CONSTRUCTION | EXPLORATION | MILITARY | SHIPPING | EVENTS

Generator Designation Fleet Range	CG-0100 844-843; 738-689
Dimensions	
Length	3280 mm
Width	1130 mm
Height	2100 mm
Weight Wet	3286 kg
Weight Dry	2720 kg
CSC Plated	No
Configuration	Canopy
Power Ratings	
Engine	1104C-44TAG2
Prime 50Hz	100 kVA
Prime 50Hz @ 0.8 pf	80 kW
Prime 60 Hz	N/A
Prime 60Hz @ 0.8 pf	N/A

Max Load @ 0.8 pf/415 V Fuel Consumption 50 Hz**

21.9 L/hr
N/A
N/A

139.1 A

Fuel Reserve 50 Hz** Tank Size 664 L 100% Load 30.3 hr 75% Load N/A 50% Load N/A Other Sound Level 66.7 dB(A) @ 7 m 45°C Temp Before Derate 47°C Maximum Operating Temperature Cooling Chamber Fan Type Direct Drive Parallel Controller Inteli-Lite Utility Configured No Telemetry Yes

Notes

** Fuel data provided as per: - includes 1 hr in 12 @ 110% Load)

- at prime rating

- ASC- Cat Application Support Centre

- dB(A) Ratings @ 100 % Load @ 50 Hz (± 2 dB(A) expected)

ONE NETWORK. ONE CALL 1800 800 441

energypower.com.au

The information in this document may change without notice. CG-0100-V1-0616



